

Product Name :

Shell & Tube Heat Exchanger for engineering schools

Product Code :

HTL0010

Description :**Shell & Tube Heat Exchanger, technical teaching equipment for engineering**

Our enterprise holds the specialization in the manufacturing, trading and exporting of optimum quality **Shell & Tube Type Heat Exchanger**.

Manufactured under strict supervision, these heat exchangers are provided with rigid MS Structure. To manufacture best quality heat exchangers, our professionals use best quality metal and latest technologies. Offered heat exchangers are easy to install and appreciated for hassle-free performance.

Description:

- Shell and Tube Heat Exchanger are popular in process industries because they occupy less space and offer reasonable temperature drop. The apparatus consists of fabricated shell, inside which tubes with baffles on outer side are fitted. The present set up is a 1-2 heat exchangers, with cold water flows through shell. Valves are provided to control the flow rates of hot and cold water. Flow rates of hot and cold water are measured using Rotameters. A magnetic drive pump is used to circulate the hot water from a re-cycled type water tank, which is fitted with heaters and Digital Temperature Controller.

The main object of the experimental setup is to study the following at various flow rates:

- LMTD
- Heat transfer rate
- Overall Heat Transfer Co-efficient

Utilities required:

- Water supply 20 lit/min (approx.) and drain.
- Electricity Supply : 1 Phase, 220 V AC, 4 kW.
- Floor area of 1.5 m x 0.75 m.

Technical Specifications:

- System: Water to Water. (1–2 shell & tube type)
- Shell:
Material Stainless steel. Insulated with ceramic wool and cladded with aluminum foil. Dia. 220 mm, Length 500 mm (Approx.)
- 25% cut baffles at 100 mm distance 4 Nos
- Tube: OD 16mm approx., Length 500mm (24 Nos.)
- Water Flow Measurement: Rotameters (2Nos.) one each for cold & hot fluid
- Hot Water Tank: Made of Stainless steel Insulated with ceramic fibre wool
- Hot Water Circulation: Magnetic Pump
- Heaters: Nichrome wire heater (2 Nos.)
- Digital Temp. Controller: 0-199.90C, (For Hot Water Tank)
- Digital Temp. Indicator: 0-199.90C, with multi-channel switch
- Temperature sensors: RTD PT-100 type

- Instruction Manual: An english instruction manual will be provided along with the Apparatus
- A good quality painted rigid MS Structure is provided to support all the parts

Technical Specification :

Shell & Tube Heat Exchanger

Naugra Export

Website: www.naugraexport.com, **Email:** sales@naugraexport.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, **Phone:** +91-0171-2643080, 2601773